



## DECLARATION OF PERFORMANCE

No. **10112202**

According Annex III of the regulation (EU) N° 305/2011

**1. Unique identification code of the product-type:**

Damex FR Adhesive

**2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):**

Damex FR Adhesive, for batch number: see packaging of the product

**3. Intended use/es:**

Sealant for façade for interior and exterior application (intended for use in cold climates)  
EN 15651-1:2012 F-EXT-INT-CC 20HM

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):**

Damex FR Ltd  
Unit 2, Purfleet Trade Parc,  
Ensign Industrial Estate, Botany Way  
Purfleet, RM19 1TB. Tel: +44 (0) 1708 926800 | Email: [info@damexfr.com](mailto:info@damexfr.com)

**5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)**

Not relevant

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**

System 3 for the type testing and System 3 for the reaction to fire

**7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**

The notified body SKZ - TeConA GmbH, D-97076 Würzburg, Friedrich-Bergius-Ring 22, identification number 1213, performed the type testing under system 3 according to EN 15651 part 1 and issued a test report.

The notified body SKZ - TeConA GmbH, D-97076 Würzburg, Friedrich-Bergius-Ring 22, identification number 1213, performed the testing of the reaction to fire under system 3 according to EN 15651 and issued a test report.

**8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**

Not relevant



### 9. Declared performance/s

EN 15651-1 F-EXT-INT-CC 20HM

Conditioning: Method B

Essential Characteristics	Performance	Harmonised Technical Specification
REACTION TO FIRE (EN13501-1)	Class B	EN 15651-1:2012
RELEASE OF CHEMICALS DANGEROUS TO THE ENVIRONMENT AND HEALTH	NPD	EN 15651-1:2012
WATER TIGHTNESS AND AIR TIGHTNESS		
Resistance to flow (EN ISO 7390)	≤3mm	EN 15651-1:2012
Loss of volume (EN ISO 10563)	≤10%	EN 15651-1:2012
Tensile properties (i.e. at maintained extensions after immersion in water at 23°C (EN ISO 10590))	NF	EN 15651-1:2012
Tensile properties (i.e. at maintained extension) for non-structural low modulus sealants used in joints in cold climate areas (-30°C) (EN ISO 8340)	NF	EN 15651-1:2012
DURABILITY (EN ISO 8340, EN ISO 9047, EN ISO 10590)	Pass	EN 15651-1:2012

NF = no failure according to ISO 11600

NPD = No performance declared

### 10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

At Purfleet, UK on 08/08/2024 by Michael Waller – Technical Director